

压敏电阻

Metal Oxide Varistor (MOV)

SFV34S H型

简介 Description




与标准型压敏电阻相比，高浪涌冲击型压敏电阻采用更高性能的材料，同尺寸产品通流能力提升30%左右，具有良好的性能和长期稳定的可靠性，可适用更高浪涌防护或者小型化的设计需求，节省空间。

Compared with standard type varistor, the high-surge impact varistor uses materials with extra high performance, having impulse capacity about 30% higher than normal varistor of the same size. Besides, the varistor has good long-term stability, and can be used in higher surge requirement or miniaturization designmen .

MOV

MOV



产品结构 Product Structure



应用领域 Applications

- 电源 Power Supplies
- 家用电器 Home Electrical Appliances
- 工业设备 Industrial Devices
- 防雷插座 Surge Protectors
- 通信电源 Telecom Devices

安规信息 Agency Approvals


认证 Agency	标准 Standards	认证号 No.
	UL 1449 4 th Edition	E322662
	CSA C22.2 NO.269.5-17	E322662

压敏电阻

Metal Oxide Varistor (MOV)

SFV34S H型


产品标识 Marking



MOV

MOV

温度降额曲线 Temp. Derating Curve



常温系列温度降额曲线
For Normal Temp. Series

备注：应用环境温度超过85 °C 时，峰值电流和能量额定值应按照上述曲线相应的降低。

Note: When ambient temp. exceeds 85 °C, the peak surge current and energy rating should be reduced as shown in left curve.

技术参数 General Technical Data

项目 Item	值 Value	单位 Unit
工作温度 Operating Temp.	-40 ~ +85	°C
存储温度 Storage Temp.	-40 ~ +125	°C
耐电压 Voltage Proof	≥2500	V _{ac}
绝缘电阻 Insulation Resistance	≥100	MΩ

型号说明 Part Numbering System

SFV 34 S 471 - K E ××××× T

性能代码 Performance Code

缺省 Default : 8/20 μ sT: 10/350 μ s

结构代码 Structure Code

E: 包封片 Encapsulating

B: 焊接片 Bare

电压公差 Voltage Tolerance

K: $\pm 10\%$ J: $\pm 5\%$

S: 特殊定制 Special Tolerance

标称压敏电压 Nominal Varistor Voltage

220: $22 \times 10^0 = 22V$ 471: $47 \times 10^1 = 470 V$ 122: $12 \times 10^2 = 1200 V$

形状 Disk Shape

S: 正方形 Square

基片尺寸 Bare Disk Dimension

正方形 S 34: 34 \times 34 mm

产品类别 Product Category

压敏电阻

Setfuse Varistor

MOV

MOV

*更多细节请参照包装信息

*For More Details Refer To Packaging Information.

术语 Glossary


项目 Item	描述 Description
V_N	标准压敏电压 Nominal Varistor Voltage 在规定持续时间的脉冲电流下测得MOV两端的电压。 Voltage, at specified D.C. current used as a reference point in the component characteristics.
I_L	漏电流 Leakage Current 在25°C或规定的其它温度下, 施加最大直流电压时, 通过压敏电阻器中的电流。 Current passing through the varistor at the max. d.c. voltage, and at a temp. of 25 °C, or any other specified temp.
UCT	上限类别温度 Upper Category Temp. 压敏电阻器设计所确定的能够连续工作的最高环境温度。 Max. ambient temp. for which a varistor has been designed to operate continuously.
LCT	下限类别温度 Lower Category Temp. 压敏电阻器设计所确定的能够连续工作的最低环境温度。 Minimum ambient temp. at which a varistor has been designed to operate continuously.
Max. Peak Current	最大峰值电流 Max. Peak Current 在环境温度25°C时, 对于规定的脉冲次数而言, 压敏电阻器中允许通过的每个脉冲的最大电流值。 Max. current per pulse, which may be passed by a varistor at an ambient temp. of 25 °C, for a given number of pulses.
V_C	箝制电压 Clamping Voltage 规定脉冲峰值电流及规定波形下测得MOV两端的电压峰值。 Peak voltage developed across the varistor terminations under standard atmospheric conditions, when passing an 8/20 μ s class current pulse.
Voltage Proof	耐电压 Voltage Proof 连续可施加在压敏电阻器引出端和导电性安装之间的最大峰值电压。 Max. peak voltage, which may be applied under continuous operating conditions between the varistor terminations and any conducting mounting surface (Applicable only to insulated varistors).
C_V	电容量 Capacitance MOV两端之间的电容量, 其测量应在规定的正弦频率和电压以及规定的温度下进行。除非另有规定, 推荐采用25°C下, 1 V _{r.m.s.} , 1 kHz的信号。 Capacitance across the MOV measured at a specified frequency and voltage.
V_{ac}	最大连续交流电压 Max. Continuous a.c. Voltage 在环境温度25°C时, 可以施加在元件上连续工作的、波形基本是正弦波(总谐波畸变小于5%)的最大交流电压有效值。当温度高于25°C时, 详细规范应给出降额曲线。 Max. a.c. r.m.s. voltage of a substantially sinusoidal waveform (less than 5% total harmonic distortion) which can be applied to the component under continuous operating conditions at 25 °C.
V_{dc}	最大连续直流电压 Max. Continuous d.c. Voltage 在环境温度25°C时, 可以施加在元件上连续工作的最大直流电压(波纹小于5%)。当温度高于25°C时, 详细规范应给出降额曲线。 Max. d.c. voltage (with less than 5% ripple) which can be applied to the component under continuous operating conditions at an ambient temp. of 25 °C.

压敏电阻

Metal Oxide Varistor (MOV)

SFV34S H型

尺寸 Dimensions (mm)



型号 Model	W	W ₁	W ₂	W ₃	H	H ₁	T	d
SFV34S241K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	4.3	0.5±0.05
SFV34S271K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	4.5	0.5±0.05
SFV34S301K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	4.7	0.5±0.05
SFV34S331K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	4.9	0.5±0.05
SFV34S361K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	5.0	0.5±0.05
SFV34S391K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	5.1	0.5±0.05
SFV34S431K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	5.2	0.5±0.05
SFV34S471K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	5.4	0.5±0.05
SFV34S511K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	5.6	0.5±0.05
SFV34S561K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	5.8	0.5±0.05
SFV34S621K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	6.1	0.5±0.05
SFV34S681K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	6.5	0.5±0.05
SFV34S751K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	6.8	0.5±0.05
SFV34S821K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	7.2	0.5±0.05
SFV34S911K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	7.6	0.5±0.05
SFV34S102K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	8.0	0.5±0.05
SFV34S112K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	8.5	0.5±0.05
SFV34S122K	37.2±1.0	34.0±1.0	25.2±0.5	14.5±0.5	11.5±0.5	6.0±0.5	9.0	0.5±0.05

MOV





MOV

压敏电阻

Metal Oxide Varistor (MOV)

SFV34S H型

技术参数 Specification

型号 Model	最大连续工作电压 Max. Continuous Operating Voltage		压敏电压 Varistor Voltage @1 mA DC		箝制电压 Clamping Voltage (Max.)		最大放电电流 Max. Discharge Current (8/20 μs)		最大能量 Max. Energy (10/1000 μs)	静态电容 Typical Capacitance (For reference only) @1 kHz	安规认证 Agency Approvals			
	VAC	VDC	Min.	Max.	V _C	I _P	I _n	I _{max}	(J)	(pF)				
	(V)	(V)	(V)	(V)	(V)	(A)	(kA)	(kA)			UL	cUL	TUV	CQC
SFV34S241K	150	200	216	264	395	300	20	50	480	5650	●	●	○	○
SFV34S271K	175	225	243	297	455	300	20	50	540	5100	●	●	○	○
SFV34S301K	190	250	270	330	500	300	20	50	600	4510	●	●	○	○
SFV34S331K	210	275	297	363	550	300	20	50	656	4150	●	●	○	○
SFV34S361K	230	300	324	396	595	300	20	50	745	3750	●	●	○	○
SFV34S391K	250	320	351	429	650	300	20	50	830	3500	●	●	○	○
SFV34S431K	275	350	387	473	710	300	20	50	920	2950	●	●	○	○
SFV34S471K	300	385	423	517	775	300	20	50	1000	2880	●	●	○	○
SFV34S511K	320	415	459	561	845	300	20	50	1060	2650	●	●	○	○
SFV34S561K	350	460	504	616	925	300	20	50	1150	2450	●	●	○	○
SFV34S621K	385	505	558	682	1025	300	20	50	1250	2200	●	●	○	○
SFV34S681K	420	560	612	748	1120	300	20	50	1250	2000	●	●	○	○
SFV34S751K	460	615	675	825	1240	300	20	50	1280	1820	●	●	○	○
SFV34S821K	510	670	738	902	1355	300	20	50	1300	1800	●	●	○	○
SFV34S911K	550	745	819	1001	1500	300	20	50	1475	1500	●	●	○	○
SFV34S102K	625	825	900	1100	1650	300	20	50	1550	1350	●	●	○	○
SFV34S112K	680	895	990	1210	1815	300	20	50	1750	1230	●	●	○	○
SFV34S122K	750	1000	1080	1320	1980	300	20	50	2000	1135	●	●	○	○

备注 Note: ● 已认证 Approved ○ 无认证 Unauthorized

MOV


MOV

焊接参数 Soldering Parameters

波峰焊参数 Wave Soldering Parameters

本波峰焊参数仅供参考，实际使用时应做相关的试验进行验证。

The wave soldering parameters are for reference only. When MOV is for practice use, some related validation is recommended.



波峰焊曲线 Wave Soldering Curve

项目 Item	温度 Temp. (°C)	时间 Time (s)
预热 Preheating	90 ~ 150	<150
过锡 Dwelling	255 ~ 290	3 ~ 10

手工焊参数 Hand-Soldering Parameters

项目 Item	条件 Condition
烙铁头部温度 Temp. of Solder Head	350 °C (max.)
焊接时间 Soldering Time	4 s (max.)


包装 Packaging Information

- 散装 Bulk Packaging (Code: BUL)
- 散装包装数量和重量 Bulk Packaging Quantity & Weight.

型号 Series	标称压敏电压 Nominal Varistor Voltage	PE袋 PE Bag	盒 Box	箱 Carton	毛重/箱 (365 × 265 × 245) G. W. / Carton
	(V)	(PCS)	(PCS)	(PCS)	(kg)±10%
34S	241 ~ 301	40	80	480	9 ~ 10
	331 ~ 821	30	60	360	7 ~ 14
	911 ~ 122	20	40	240	10 ~ 13

备注：其它脚长包装信息请咨询赛尔特。
 Note: Other lead length packaging information, please contact SETsafe | SETfuse.

单位 Dimensions (mm)





注意 ATTENTION

使用 Usage

1. 压敏电阻的使用环境温度不能超出技术条件规定的范围。
Varistor must operate within the specified ambient temp.
2. 请不要用酮类、酯类、苯类、卤代烃等强极性溶剂清洗本产品，以免破坏产品的封装层。
Do not clean the varistor with strong polar solvent such as ketone, esters, benzene, halogenated hydrocarbon, to avoid damaging the encapsulating layer.
3. 请不要强烈的振动、冲击或施加压力，以免压敏电阻表面树脂或元件产生裂痕。
Please do not apply severe vibration, shock or pressure to MOV, to avoid surface resin or element cracking.
4. 对引线进行弯曲加工或切断加工时，请固定元件端引线。折弯距离引线绝缘覆盖部分至少2 mm。
Please fix lead wires when bending or cutting. The distance between the bending point and the sealing of MOV shall be greater than 2 mm.

更换 Replacement

如发现压敏电阻外观有损伤，请更换。
If varistor is visually damaged, please replace it.

贮存 Storage

1. 存储温度：Storage Temp. Range: (-40 to +125) °C
2. 相对湿度：Relative Humidity: ≤75% RH
3. 海拔高度：Altitude: <2000 m

4. 压敏电阻的存储应避免高温、高湿、阳光直射和腐蚀性气体的场合，以免影响引脚的可焊性，产品出厂后请于1年内使用。

Do not store the MOV at the high temp., high humidity or corrosive gas environment, to avoid influencing the solder-ability of the lead wires, the product shall be used up within 1 year after receiving the goods.

不适宜环境条件 Environmental Conditions

1. 压敏电阻不应直接暴露在露天工作。
Varistor should not be exposed to the open air.
2. 压敏电阻应避免在雨水，水蒸汽等高温高湿的条件下工作。
Varistor should avoid rain, water vapor or other condition of high temp. and high humidity.
3. 压敏电阻应避免在沙尘、盐雾、有害气体的条件下工作。
Varistor should avoid sand dust, salt spray, or other harmful gases.

压敏电阻的固有电容 Max. Typical Capacitance of Varistor

压敏电阻的固有电容最大参考值已在规格表中列出，供设计师在高频电路中选用时参考。
The typical capacitance of varistor is listed in the specifications. Designers may refer to it when designing MOV in high frequency circuit.

安装 Installation

机械应力 Mechanical Stress

安装时应避免敲击压敏电阻，以免造成机械损伤。

Do not knock MOV when installing, to avoid mechanical damage.