


简介 Description

厦门赛尔特电子有限公司自主研发的T1防雷型压敏电阻具有高通流容量，特别是对10/350 μ S冲击放电电流具有优异的耐受能力，同时具有良好的交直流特性，可满足建筑物、光伏及风电等应用场景的防雷需求。

The T1 surge protection type varistor selfdeveloped by Xiamen SET Electronics Co., Ltd. has high surge current capacity, especially outstanding 10/350 μ s impulse capacity, and good AC & DC characteristics. It suits all the surge protection scenarios of buildings, photovoltaic and wind power applications.


产品结构 Product Structure



安规信息 Agency Approvals

认证 Agency	标准 Standards	认证号 No.
	UL 1449 4 th Edition	On-going
	CSA C22.2 NO.269.5-17	On-going

尺寸 Dimensions (mm)



W	W ₁	H	H ₁	t (min.)
44.2±0.8	38.5±0.5	29.5±0.8	23.9±0.5	0.8

*可定制各种电极形状的焊接片及封装片
 Various electrode shapes of uncoated MOV or coated MOV can be customized

压敏电阻

Metal Oxide Varistor (MOV)

YMJ36R T型

技术参数 Specification

型号 Model	浪涌 等级 Surge Level	最大连续工作电压		压敏电压		箝制电压		最大峰值电压		冲击放电电流	最大能量	静态电容
		Max. Continuous Operating Voltage		Varistor Voltage @1 mA DC		Clamping Voltage (Max.)		Max. Discharge Current (8/20 μ s)		Impulse Discharge Current (10/350 μ s)	Max. Energy (10/1000 μ s)	Typical Capacitance (Reference) @1 kHz
		Vac	Vdc	Min.	Max.	V _C	I _P	I _n	I _{max}	I _{imp}	(J)	(pF)
		(V)	(V)	(V)	(V)	(V)	(A)	(kA)	(kA)	(kA)		
YMJ36R241K	T	150	200	216	264	395	200	25	50	8.5	575	5650
YMJ36R271K	T	175	225	243	297	455	200	25	50	8.5	650	5100
YMJ36R301K	T	190	250	270	330	500	200	25	50	8.5	720	4510
YMJ36R331K	T	210	275	297	363	550	200	25	50	8.5	780	4150
YMJ36R361K	T	230	300	324	396	595	200	25	50	8.5	900	3750
YMJ36R391K	T	250	320	351	429	650	200	25	50	8.5	1000	3500
YMJ36R431K	T	275	350	387	473	710	200	25	50	8.5	1100	2950
YMJ36R471K	T	300	385	423	517	775	200	25	50	8.5	1200	2880
YMJ36R511K	T	320	415	459	561	845	200	25	50	8.5	1250	2650
YMJ36R561K	T	350	460	504	616	925	200	25	50	7.5	1350	2450
YMJ36R621K	T	385	505	558	682	1025	200	25	50	7.5	1500	2200
YMJ36R681K	T	420	560	612	748	1120	200	25	50	7.0	1500	2000
YMJ36R711K	T	440	585	639	781	1170	200	25	50	7.0	1550	1900
YMJ36R751K	T	460	615	675	825	1240	200	25	50	7.0	1550	1820
YMJ36R821K	T	510	670	738	902	1355	200	25	50	6.0	1550	1800
YMJ36R911K	T	550	745	819	1001	1500	200	25	50	6.0	1750	1500
YMJ36R951K	T	575	760	855	1045	1565	200	20	50	5.0	1800	1400
YMJ36R102K	T	625	825	900	1100	1650	200	20	50	5.0	1850	1350
YMJ36R112K	T	680	895	990	1210	1815	200	20	50	5.0	2100	1230

★每只压敏电阻可同时进行I_n/I_{max}/I_{imp}冲击。The I_n/I_{max}/I_{imp} could be applied to the same varistor.

★DC应用有特定产品，选购时需注明。

We have specified product for DC application, please make a note when purchasing.

MOV

MOV